



POSITAL

FRABA

LINARIX Linear Sensor

LU0-C901B-1212-2S0A-5AW



General Data

General Data

Supply Voltage	9 - 30 VDC
Power Consumption	≤ 1.2 W
Turn On Time	<500 ms
Operating Temperature	-30 °C fixed (-22 °F), -5 °C flexible (+23 °F) - +80 °C (+176 °F)
Weight	680 g (1.50 lb)
Protection Class (Encoder)	IP54
EMC: Emitted Interference	DIN EN 61000-6-4
EMC: Noise Immunity	DIN EN 61000-6-2

Mechanical Data

Max. Measurement Length	2.40 m (7.87')
Length per Revolution	150.8 mm
Wire Material	Coated Polyamide Stainless Steel
Wire Diameter	0.45 mm
Encoder Housing Material	Steel
Draw Wire Housing Material	Plastic
Max. Speed of Wire Displacement	1.0 m / s
Max. Wire Acceleration	5.0 g

Data Sheet
Printed at 11-06-2019 02:06



POSITAL

FRABA

Max. Extension Force	7.0 N
Min. Retraction Force	1.0 N
Actuation Lifetime	1.0 mio Cycles
Wire Mounting	Wireclip

Sensor Data

Technology	Magnetic ($\leq 0.09^\circ$)
Accuracy	± 0.10 % FSO
Repeatability	± 0.04 % FSO
Resolution [Encoder - Singleturn]	12 bit
Resolution [Encoder - Multiturn]	12 bit
Approx. Linear Resolution	36.8 μm
Output Code	Binary

Interface

Communication Interface	SAE J1939
Profile	J1939 specific
Programming Functions	Resolution, preset, direction, node ID, baud rate
Manual Functions	Programmable
Transmission Rate	min. 20 kBaud, max. 1 MBaud
Cycle Time Interface	≥ 1 ms

Outputs

Output Driver	Transceiver (ISO 11898), Galvanically Isolated by Opto-Coupl
Current Consumption	≤ 70 mA @ 10 V DC, ≤ 50 mA @ 24 V DC
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes
MTTF	240 years @ 40 °C

Electrical Connection

Connection Orientation	Axial
Connection Orientation (w.r.t Draw Wire)	Radial 0 / Axial
Connection Type	Cable / Connector
Cable Length	5 m [197"]
Wire Cross Section	0.14 mm ² / AWG 26
Material / Type	PVC



POSITAL

FRABA

Cable Diameter	6 mm (0.24 in)
Minimum Bend Radius	46 mm (1.81") fixed, 61 mm (2.4") flexing

Product Life Cycle

Product Life Cycle	New
--------------------	-----

Connection Plan

SIGNAL	CABLE COLOR
Power Supply	Red
GND	Yellow
CAN High	White
CAN Low	Brown
CAN GND	Green

Connector-View on Encoder
Dimensional Drawing

[2D Drawing](#)

Contact



Contact Us

All dimension in [inch] mm. Encoder dimensions may vary depending on electrical interface and connector. This drawing and the information contained is for general presentation purposes only. Please refer to the "Download" section for detailed technical drawings. © FRABA B.V., All rights reserved. We do not assume responsibility for technical inaccuracies or omissions. Specifications are subject to change without notice.