

94 dB/125 Hz

SOUND CALIBRATOR

Model : SC-943

ISO-9001, CE, IEC1010



Lutron



LUTRON ELECTRONIC

The Art of Measurement

94 dB/125 Hz

SOUND CALIBRATOR

Model : SC-943

FEATURES

Standard 94 dB/125 Hz
Sound calibrator, useful to calibrate another "
Sound Level Meter " precisely.

General/ Electrical Specification (23 ±5°C)

Frequency	125 Hz ±2%
Sound Pressure Level (at 23 ±5°C)	94 dB ±0.75 dB. * <i>Spec. tested under the environment RF Field Strength less than 3 V/M & frequency less than the 30 MHz only.</i>
Suitable Microphone Type	1 " mic. & 0.5 " mic. * <i>0.5" microphone is calibrated with 0.5" mic. adapter(standard acc.)</i>
Distortion	94 dB range harmonic distortion : 3 %.
Operating Temp.	0 °C to 50 °C (32 °F to 122 °F).
Power Supply	DC 9 V battery (006P, 6F22) x 2 PCs. * <i>Recommend use the Alkaline or Heavy duty type battery.</i>
Power Consump.	Approx. DC 10.6 mA (in BAT.TEST position) Approx. DC 2.3 mA (in ON position)
Battery Check	Build in " Low Battery Indicator "
Dimension	Dia 50 mm (round) x 145 mm (length).
Weight	Approx. 277 g/0.61 LB (meter only).
Accessories Included	Instruction manual..... 1 PC. 0.5" mic. adapter..... 1 PC. Adjust Screw Driver..... 1 PC. Carrying case, CA-03..... 1 PC.