



OEM Pressure Transmitter TSA-1200PT

**12 MONTH
WARRANTY**

Features of the TSA-1200PT


- Pressure Type: Gauge Pressure*
- Working Temperature: -40°C~100°C
- Compensated Temperature: -10°C~80°C
- Storage Temperature: -50°C~125°C
- Signal Output: 4~20mA (0.5~4.5V)*
- Accuracy: $\pm 0.5\%$
- Power Supply: 10~30Vdc
- Protection: IP67 with M12 Plug & TSA Connector
- Process Connection: 1/4 BSPP*
- Material: Stainless Steel, Cr18Ni9Ti & Ceramic
- Overload Pressure; 1.5 x Rated Pressure (Max. 3 x RP)
- Approvals: CE, RoHS Approved
- EMI: EN50081-1/-2; ENS: EN50082-2

*Other options available



Specifications

Dimensions (mm)




Applications

- Industrial
- Air Compressors
- Building Water Supply Systems
- Hydraulic Control
- Air Conditioners
- Automotive Industry
- Heating Systems
- Refrigeration

Electrical Connection

- Pin (2-Wire)
 1 Power Supply
 2 NC
 3 Output Signal +
 4 Shield



Order Code

TSA-1200PT-0000AB-MA5
 TSA-1200PT-0001AB-MA5
 TSA-1200PT-0005AB-MA5
 TSA-1200PT-0010AB-MA5
 TSA-1200PT-0016AB-MA5
 TSA-1200PT-0025AB-MA5
 TSA-1200PT-0050AB-MA5
 TSA-1200PT-0100AB-MA5
 TSA-1200PT-0200AB-MA5
 TSA-1200PT-0300AB-MA5
 TSA-1200PT-0400AB-MA5
 TSA-1200PT-0500AB-MA5
 TSA-1200PT-0600AB-MA5

Range

-1~0bar (-100kpa) (-14.5psi)
 0~1bar (100kpa) (14.5psi)
 0~5bar (500kpa) (72.5psi)
 0~10bar (1000kpa) (145psi)
 0~16bar (1600kpa) (232psi)
 0~25bar (2500kpa) (362.5psi)
 0~50bar (5000kpa) (725psi)
 0~100bar (10Mpa) (1450psi)
 0~200bar (20Mpa) (2900psi)
 0~300bar (30Mpa) (4351psi)
 0~400bar (40Mpa) (5800psi)
 0~500bar (50Mpa) (7252psi)
 0~600bar (60Mpa) (8702psi)

Plug Cable

M12-S4P-5M:
 M12 locking plug, straight,
 4 Pin, 5M Cable, Black, shielded



Options

Output Signals: 4-20mA (MA5), 0-5V (MB5), 0.5-4.5 (MC5), 0-10V (MD5)
Process Connections: 1/4" BSP (AB), 1/2" BSPP (AC), 1/4" NPT (AM), 7/16UNF (AU), M20x1.5 (AE)
Supply Voltage: 12-30VDC, 24Vac2, 5VDC
Connectors: Packard, DIN43650C, DIN72585